



**IC-F1100D** Series  
**IC-F2100D** Series

**VHF AND UHF DIGITAL TRANSCEIVERS**

## Big on Audio, Small on Size 1500 mW Class Leading Audio

The IC-F1100D and IC-F2100D IDAS™ digital handheld units improve on the past performance of the IC-F1000D and IC-F2000D as well as setting a new standard in digital communication. This model continues Icom's reputation for high power audio clarity with a leading edge 1500 mW speaker. These compact handheld radios are also waterproof, dustproof and come with a long lasting battery for those times when communication matters. The digital handheld units are available in three designs which are Simple version with no display or keypad (IC-F1100D & IC-F2100D), simple keypad and display version (IC-F1100DS & IC-F2100DS) and Full keypad and display version (IC-F1100DT & IC-F2100DT).

**Icom's custom high power handling capacity speaker for 1500 mW of powerful audio**

**Compact, waterproof durable design (IP67/55/54 and MIL-STD-810-G)**

**Over-the-Air Alias (OAA) function displays the caller's name without programming (IC-F1100DT/DS and IC-F2100DT/DS only)**

**AquaQuake™ function clears any water ingress that may penetrate the speaker grill of the unit**

**Motion/Stationary detection, Man Down and Lone Worker functions**

**Operating time of up to 18 hours with the supplied battery (BP-280)**

**IDAS™ conventional and Type-D single-site trunking**



IC-F1100DT

IC-F2100DS

IC-F1100D

**IDAS™** **NXDN™**  
ICOM DIGITAL ADVANCED SYSTEM

## General Features

- 136–174, 350–400, 400–470, 450–520 MHz versions
- 128 Channels / 8 Zones (for LCD types)
- 16 Channels (for non-display types)
- Icom's customized speaker offers a louder 1500 mW audio output
- An engineered casing that amplifies and improves acoustic sound clarity
- Compact (52.2 (W) × 111.8 (H) mm; 2.1 × 4.4 in) and light-weight
- IP67/55/54 waterproof and dust-tight protection
- Tested to 12 categories of MIL-STD-810-G environmental tests
- AquaQuake™ – Expels water ingress from the speaker grill
- DTMF autodial memories
- 16-position rotary selector and ON/OFF volume knob
- Programmable keys – Increase the number of programmable key assignments by using the “Shift key”
- Operating times of up to 18 hours (with the supplied BP-280 battery pack)
- Eight character alphanumeric display (for LCD types)
- Three color LED



1500 mW powerful audio



Icom custom high power handling capacity speaker



Waterproof for 30 minutes in one meter depth of water

## Operating Mode

- NXDN conventional
- NXDN multi-site conventional over IP network
- NXDN Type-D single-site trunking
- Analog mode
- Analog/digital mixed operation



Check our website to know more about 6.25 kHz FDMA narrow band.  
[www.icom.co.jp/world/fdma/](http://www.icom.co.jp/world/fdma/)

## Digital Functions (Voice and Data)

- AMBE+2™ vocoder
- Over-the-Air Alias (OAA) displays the caller's name without programming (for LCD types)
- Individual, Group and All call
- Late entry for Group call
- Status call and Polling
- Short data messages (for LCD types)
- Call alert
- Radio check (RX only)
- GPS position capabilities (requires HM-171GPW)

## Analog Functions

- CTCSS and DTCS tone
- 2-Tone and 5-Tone
- MDC PTT ID transmission
- BIIS PTT ID transmission

## Safety and Security

- Digital voice scrambler (Low level encryption)
- Radio Stun/Revive/Kill (RX only)
- Remote monitor
- Man down, Lone worker and Emergency call key capability
- Motion and Stationary detection function
- Surveillance function temporarily turns OFF the beep and LED indicator
- Power ON password (for LCD types)

## Scan Functions

- Priority scan monitors one or two priority channels while scanning non-priority channels
- Voting scan automatically selects the optimal repeater site
- Mode dependent scan automatically changes the scan list, depending on the operating channel
- Power ON scan function
- Talk Back timer

## Voice/Audio Functions

- Channel announcement function
- VOX function for hands-free operation
- Siren sound for security alarm

	IC-F1100DT/DS	IC-F1100D	IC-F2100DT/DS	IC-F2100D
<b>GENERAL</b>				
Frequency coverage* (* Varies, depending on the version)	136–174 MHz		350–400 MHz (EXP) 400–470 MHz (ALL) 450–520 MHz (USA, EXP)	
Number of channels	128 channels/ 8 zones	16 channels	128 channels/ 8 zones	16 channels
Type of emission* (* Depends on the version)	11K0F3E, 4K00F1D (USA) 16K0F3E, 14K0F3E, 11K0F3E, 8K50F3E, 4K00F1D (EXP) 16K0F3E, 14K0F3E, 8K50F3E, 4K00F1D (EUR)			
Power supply requirement	7.5 V DC nominal			
Current drain (approximate)	Tx 1.3 A		1.4 A	
	Rx 520 mA /110 mA (Max. audio (internal SP)/Standby)		520 mA /110 mA (Max. audio (internal SP)/Standby)	
Antenna impedance	50 Ω			
Operating temperature range	–30°C to +60°C; –22°F to +140°F (Radio specification) (USA/EXP) –25°C to +55°C (Radio specification) (EUR)			
Dimensions (W × H × D; Projections not included)	IC-F1100DS/D, IC-F2100DS/D: 52.2 × 111.8 × 29.4 mm; 2.1 × 4.4 × 1.2 in (With BP-280) IC-F1100DT, IC-F2100DT: 52.2 × 111.8 × 34.1 mm; 2.1 × 4.4 × 1.3 in (With BP-280)			
Weight (approximate)	IC-F1100D, IC-F2100D: 260 g; 9.2 oz (With BP-280 and MB-133) IC-F1100DS, IC-F2100DS: 270 g; 9.5 oz (With BP-280 and MB-133) IC-F1100DT, IC-F2100DT: 280 g; 9.9 oz (With BP-280 and MB-133)			
<b>TRANSMITTER</b>				
Output power (Hi, L2, L1)	5 W, 2 W, 1 W		4 W, 2 W, 1 W	
Maximum frequency deviation	± 5.0 kHz (25 kHz), ±4.0 kHz (20 kHz), ±2.5 kHz (12.5 kHz)			
Spurious emissions	70 dB minimum (USA) 0.25 μW (≤ 1 GHz), 1.0 μW (> 1 GHz) (EUR/EXP)			
Frequency stability	±1.0 ppm			
Audio harmonic distortion	0.7% typ. (25 kHz), 0.9% typical (20 kHz), 1.0% typical (12.5 kHz) (at AF 1 kHz 40% deviation)			
FM Hum and Noise (without CCITT filter)	40 dB typical (12.5 kHz) (USA)		44 dB typical (12.5 kHz) (USA)	
Residual modulations (with CCITT filter)	52 dB typical (25 kHz), 50 dB typical (20 kHz), 46 dB typical (12.5 kHz) (EUR/EXP)		54 dB typical (25 kHz), 52 dB typical (20 kHz), 48 dB typical (12.5 kHz) (EUR/EXP)	
FSK error	5% maximum			
External microphone connector	3-conductor 2.5 (d) mm (1/10)/2.2 kΩ			
<b>RECEIVER</b>				
Sensitivity	(at 12 dB SINAD)	0.21 μV typical		0.24 μV typical
	(at 20 dB SINAD)	–4 dBμV typical emf		–5 dBμV typ. emf (25/20 kHz), –2 dBμV typ. emf (12.5 kHz)
	(at 5% BER)	–8 dBμV typical emf (0.20 μV typical)		
Adjacent channel selectivity	77 dB typ. (25 kHz), 74 dB typ. (12.5 kHz), 69 dB typ. (12.5 kHz), 59 dB typ. (digital)		76 dB typ. (25 kHz), 75 dB typ. (12.5 kHz), 69 dB typ. (12.5 kHz), 58 dB typ. (digital)	
Spurious response rejection	80 dB typical			
Intermodulation rejection	75 dB typ. (25/12.5 kHz), 71 dB typ. (digital) (USA/EXP) 69 dB typ. (25/20/12.5 kHz), 74 dBμV emf typ. (digital) (EUR)		77 dB typ. (25/12.5 kHz), 70 dB typ. (digital) (USA/EXP) 70 dB typ. (25/20/12.5 kHz), 74 dBμV emf typ. (digital) (EUR/EXP)	
Hum and noise	(With CCITT filter)	47 dB typ. (25 kHz), 43 dB typ. (12.5 kHz) (USA/EXP)		42 dB typical (12.5 kHz) (USA)
	(Without CCITT filter)	52 dB typ. (25 kHz), 50 dB typ. (20 kHz), 46 dB typ. (12.5 kHz) (EUR)		50 dB typ. (25 kHz), 48 dB typ. (20 kHz), 45 dB typ. (12.5 kHz) (EUR)
AF output power (at 5% distortion)	Internal SP	1500 mW typical (With an 8 Ω load)		
	External SP	400 mW typical (With an 8 Ω load)		
External speaker connector	2-conductor 3.5 (d) mm (1/8)/8 Ω			

All stated specifications are subject to change without notice or obligation. Measurements made in accordance with TIA-603 (USA/EXP) or EN 300-086, EN 301-166 (EUR). The IC-F1100DT/DS/D VHF versions are under evaluation as of May 2018.

### Applicable U.S. Military Specifications & IP Rating

Standard	MIL 810G	
	Method	Procedure
Low Pressure	500.5	I, II
High Temperature	501.5	I, II
Low Temperature	502.5	I, II
Temperature Shock	503.5	I-C
Solar Radiation	505.5	I
Rain Blowing/Drip	506.5	I, III
Humidity	507.5	II
Salt Fog	509.5	–
Dust Blowing	510.5	I
Immersion	512.5	I
Vibration	514.6	I
Shock	516.6	I, IV

Also meets equivalent MIL-STD-810-C, -D, -E and -F.

Ingress Protection Standard			
Dust & Water		IP67/55/54	
Battery Life			
Battery pack	Type	Capacity	Operating time*
BP-280	Li-ion 7.2 V	2400 mAh (typ.), 2280 mAh (min.)	Up to 18 hours
BP-279	Li-ion 7.2 V	1570 mAh (typ.), 1485 mAh (min.)	Up to 11.5 hours
BP-278	Li-ion 7.2 V	1190 mAh (typ.), 1130 mAh (min.)	Up to 9 hours

\* TX: RX: standby = 5:5:90. Power save function ON.

**Supplied accessories:** (May differ, or not supplied, depending on version)  
 • Battery pack, BP-280 • Belt clip, MB-133 • Antenna  
 • Desktop charger, BC-213\* • AC adapter, BC-123SE\*



The "3D GENUINE Icom label" is attached to the rear chassis under the battery. Check the Icom website for details: <http://www.icom.co.jp/world/genuine-info/>

**BATTERY PACKS**

**BP-278:** 1190 mAh (typ.), 1130 mAh (min.) rechargeable Li-ion battery.

**BP-279:** 1570 mAh (typ.), 1485 mAh (min.) rechargeable Li-ion battery.

**BP-280:** 2400 mAh (typ.), 2280 mAh (min.) rechargeable Li-ion battery.



BP-278

BP-279

BP-280

**BATTERY CHARGERS**

**BC-213:** Desktop charger.

Charges the BP-278, BP-279 or BP-280. Charges the BP-280 in 3.5 hours (approximate).

+ **BC-123SA/SE/SUK/SV:** AC adapter.

**BC-214:** Multi-charger.

Charges up to six radios and/or batteries at the same time.

+ **BC-157S:** AC adapter.

\* AD-130 charger adapter is supplied with the BC-214, depending on the version.



BC-213

BC-123SA

BC-214

BC-157S

**POWER SUPPLY CABLES AND CHARGER BRACKET**

**CP-23L:** Vehicle charger cable for use with the BC-213.

**OPC-656:** DC power cable for use with the BC-214.

**MB-130:** Charger bracket for use with the BC-213.



CP-23L

OPC-656

MB-130

**SPEAKER-MICROPHONES**

**HM-171GPW:** GPS speaker microphone with a waterproof connector. IP67 protection.

**HM-168LWP:** Waterproof speaker microphone with a waterproof connector. IP67 protection.

**HM-159LA:** Speaker microphone with a 3.5 mm earphone jack.

**HM-158LA:** Compact speaker microphone with a 3.5 mm earphone jack.



HM-171GPW

HM-168LWP

HM-159LA

HM-158LA

**EARPHONE-MICROPHONES**

**HM-153LA:** Durable lapel microphone with earphone.

**HM-166LA:** Light weight lapel microphone with earphone.



HM-153LA

HM-166LA

**HEADSETS, PTT SWITCH CABLE & PLUG ADAPTER**

**HS-94LWP:** Earphone-headset with a waterproof connector.

**HS-95LWP:** Behind-the-head headset with a waterproof connector.

**HS-94:** Earphone-headset. (Use with either the VS-4LA or OPC-2004LA)

**HS-95:** Behind-the-head headset. (Use with either the VS-4LA or OPC-2004LA)

**HS-97:** Throat microphone. (Use with either the VS-4LA or OPC-2004LA)

**VS-4LA:** PTT switch cable for manual PTT operation.

(For use with either the HS-94, HS-95 or HS-97)

**OPC-2004LA:** Plug adapter cable for VOX operation.

(For use with either the HS-94, HS-95 or HS-97)



HS-94LWP

HS-95LWP

HS-97

VS-4LA

OPC-2004LA

**BELT CLIP**

**MB-133:** Alligator belt clip. Same as supplied.

**SOFTWARE AND CABLE**

**CS-F2100D:** Programming software.

**OPC-478UC:** USB type radio programming cable.

**ANTENNAS**

**FA-SC25V:** 136–150 MHz

**FA-SC55V:** 150–174 MHz

**FA-SC25U:** 400–430 MHz

**FA-SC57U:** 430–470 MHz

**FA-SC72U:** 470–520 MHz

**FA-SC01U:** 350–400 MHz

**FA-SC02U:** 330–380 MHz



FA-SC25V

FA-SC55V

FA-SC25U

FA-SC57U

FA-SC72U

FA-SC01U

**HIGH GAIN ANTENNAS**

**FA-SC62V:** 150–160 MHz

**FA-SC63V:** 155–165 MHz



FA-SC62V

FA-SC63V

**STUBBY ANTENNAS**

**FA-SC26VS:** 136–144 MHz

**FA-SC27VS:** 142–150 MHz

**FA-SC56VS:** 150–162 MHz

**FA-SC57VS:** 160–174 MHz

**FA-SC26US:** 400–450 MHz

**FA-SC73US:** 450–490 MHz



FA-SC26VS

FA-SC27VS

FA-SC56VS

FA-SC57VS

FA-SC26US

FA-SC73US

**CUT-TYPE ANTENNAS**

**FA-SC61VC:** 136–174 MHz

**FA-SC61UC:** 380–520 MHz



FA-SC61VC

FA-SC61UC

Some options may not be available in some countries. Please ask your dealer for details.

Icom, Icom Inc. and Icom logo are registered trademarks of Icom Incorporated (Japan) in Japan, the United States, the United Kingdom, Germany, France, Spain, Russia, Australia, New Zealand and/or other countries. IDAS, IDAS logo and AQUA-QUAKE are trademarks of Icom Incorporated. NXDN is a trademark of Icom Incorporated and JVC KENWOOD Corporation. AMBE+2 is a trademark and property of Digital Voice System, Inc. All other trademarks are the properties of their respective holders.

**Icom Inc.** 1-1-32, Kamiminami, Hirano-Ku, Osaka 547-0003, Japan Phone: +81 (06) 6793 5302 Fax: +81 (06) 6793 0013

[www.icom.co.jp/world](http://www.icom.co.jp/world)

**Count on us!**

**Icom America Inc.**  
[www.icomamerica.com](http://www.icomamerica.com)

**Icom (Europe) GmbH**  
[www.icomeurope.com](http://www.icomeurope.com)

**Icom (Australia) Pty. Ltd.**  
[www.icom.net.au](http://www.icom.net.au)

Your local distributor/dealer:

**Icom Canada**  
[www.icomcanada.com](http://www.icomcanada.com)

**Icom Spain S.L.**  
[www.icomspain.com](http://www.icomspain.com)

**Shanghai Icom Ltd.**  
[www.bjicom.com](http://www.bjicom.com)

**Icom Brazil**  
E-mail: [sales@icombrasil.com](mailto:sales@icombrasil.com)

**Icom (UK) Ltd.**  
[www.icomuk.co.uk](http://www.icomuk.co.uk)

**Icom France s.a.s.**  
[www.icom-france.com](http://www.icom-france.com)